

| 1987 CAN-AM SPECIFICATIONS | | | | |
|--|--|---------|-----------------------|-----------|
| MODELS | 200 ASE | 250 ASE | 406 ASE | 500 ASE |
| ROTAX ENGINE | | | | |
| Displacement (cc) | 199.3 | 248.4 | 399 | 482.3 |
| Bore (mm) | 64.5 | 72 | 84 | 85 |
| Stroke (mm) | 61 | 61 | 72 | 85 |
| Premix | 40:1 | 40:1 | 32:1 | 25:1 |
| Clutch Plates | 5 | 6 | 8 | 8 |
| Gears | 6 | 6 | 5 | 5 |
| Mikuni carburetor | VM-34 | VM-34 | VM-38 | VM-38 |
| Bosch Plug | W300TZ | W275TZ | W275TZ | W275TZ |
| Eng/Rear Sprockets | 14/46 | 14/46 | 14/46 | 19/46 |
| CHASSIS | | | | |
| Dry Weight (Kg/lbs) | 99/218 | 100/220 | 104.1/229 | 111.5/246 |
| Steering angle | 27 | 27 | 27 | 28 |
| Wheelbase | 146.7 cm (57.75 in) | | 151.1 (59.49) | |
| Seat Height | 94.6 cm (37.25 in) | | 96.5 (37.99) | |
| Ground Clearance | 35.3 cm (14 in) | | | |
| Fuel Capacity | 12 L (3.25 US gal, 2.73 Imp gal) | | | |
| Travel F/R mm (in) | 300 mm (11.8 in) / 317.5 mm (12.5 in) | | | |
| Linkage | Direct Link | | QuadLink II | |
| Brakes F/R | 240 mm Grimeca disc/140 mm leading shoe drum | | | |
| Front Tire | Metzeler 3.00 x 21 | | | |
| Rear Tire | Metzeler MX 4.50 x 18 | | Metzeler MXR 180 x 90 | |
| Features: Primary kick starting, Akront rims, Reynolds 531 tube frame, Regina RC520 chain, Quick-detach rear wheel with snail-cam chain adjusters, Bosch CDI ignition, Marzocchi 42 mm M1 forks, compression and rebound adjustable White Power piggyback shock, Kickstand, re-settable odometer, muffler/spark arrestor, Enduro lighting, quick service airbox, unleaded fuel, aluminum sub-frame. | | | | |



Can-Am 300AT

Every trials rider dreams of perfect balance and predictable power. Can-Am has built that dream. Smooth-acting Marzocchi forks. White Power - assisted QuadLink II. mono-shock system. Responsive Rotax engine. Aluminum frame. Precisely what you need to win!

| | |
|---------------|-------------------|
| Engine | 276 cc |
| Bore | 76 mm |
| Stroke | 61 mm |
| Transmission | 6 spds |
| Sprockets | 12T/40T |
| Seat Height | 73.6 cm (29") |
| Wheelbase | 130.2 cm (51.25") |
| Clearance | 315 mm (12.4") |
| Steering head | 25.75 |
| Weight (dry) | 87.3 kg (192 lbs) |



can-am®



...it's easy to clean up!